



## SLIM RECESSED

### Descrizione tecnica:

Apparecchio tondo ad incasso a scomparsa totale con innesto rapido e alimentatore posto in remoto. Struttura in alluminio verniciato a polveri epossilpoliestere in nitura bianco, anodizzato nero e bronzo.

L'apparecchio di una lente asferica standard in vetro per un'emissione a 26°.

Cablato con sorgente luminosa a LED COB ad alta potenza.

Compreso di alimentatore 150mA solo per montaggio a remoto.

### Installazione:

Ad incasso con plasterkit.



### Dimensioni:

SLIM RECESSED

Ø = 30 mm H = 80 mm

### Colore:



Nero



Bianco



Bronzo



SLIM 5,5W, 700lm, CRI>90, 3000°K

Disponibile con dimmerazione DALI.



Disponibile nella versione 2700°K e 4000°K.

SLIM RECESSED





## SLIM RECESSED

### Technical description:

Round recessed luminaire with total disappearance with quick coupling and power supply remotely placed. Aluminum structure painted with epoxy-polyester powders in white, black anodized and bronze finish.

The fixture of a standard aspherical glass lens for a 26 ° emission.

Wired with high power COB LED light source.

Including 150mA power supply for remote mounting only.

### Installation:

Recessed with plasterkit.



### Dimension:

SLIM RECESSED

Ø = 30 mm H = 80 mm

### Finishes:



SLIM 5,5W, 700lm, CRI>90, 3000°K

Available with DALI dimmeration.



Available in 2700°K and 4000°K version.

SLIM RECESSED

