

Technical product sheet

Progetto mad designer 2014

MACROLUX

MACROLUX s.r.l. 31020 San Vendemiano Treviso - Italia Via Padania, 67/69 t. +39 0438 470773 f. +39 0438 470295 p. iva 03547130264 macrolux@macrolux.net www.macrolux.it



RC_110

Technical description

Round recessed luminaire with total disappearance in plasterboard made of aluminum in the silk white and matt black finishes, with a cylindrical projector integrated adjustable telescopic in silk white and matt black finishes.

The projector is equipped with a black anodized ring to reduce the luminances, removable up to one centimeter for a decorative effect.

Possibility to wire COB LED light sources with 3 McAdams color tolerance, operating life 50.000 hours, emission degrees 20 ° and 34 °, CRI> 90, Class A ++.








Installation:

Recessed plasterboard.

Dimensions:

RC_110 Ø cassa=176mm Ø Spot=60mm Ø Incasso=110mm
H1=181mm H2=139mm H3=42mm

Colore:

 	= 22	 	= 42
incasso nero + proiettore nero black trimless + black projector		incasso bianco + proiettore nero white trimless + black projector	
 	= 44	 	= 24
incasso bianco + proiettore bianco white trimless + white projector		incasso nero + proiettore bianco black trimless + white projector	

RC110 LED COB 9W 3000°K 1025lm 114lm/W CRI>90 500mA clas. A++

IP 40      

Available in 2700 ° K - 4000 ° k

RC_110

Adjustability +/- 24 °

