



SPOT LED 70 per ZERO

Descrizione tecnica:

Apparecchio orientabile +/- 90° in alluminio nero opaco con struttura telescopica, orientabile tramite bracci meccanici snodati. Il posizionamento degli spot nel canale viene effettuato mediante l'uso di un magnete, che consente il cambio di posizione e/o l'integrazione in qualsiasi momento.

Installazione:

Per sistemi ZERO ed f_90/140



Dimensioni:

SPOT LED 70

Ø = 65 mm H = 82/100mm

Colore:





SPOT LED 70 6W 615lm 102,5lm/W 350mA 3000°K CRI>90
SPOT LED 70 9W 1025lm 114lm/W 500mA 3000°K CRI>90

Disponibile con dimmerazione DALI.



Disponibile nella versione 2700°K e 4000°K.

SPOT LED 70





SPOT LED 70 per ZERO

Technical description:

+/- 90° adjustable fixture in matt black aluminum with telescopic structure, adjustable by mechanical jointed arms. The positioning of the spots in the channel is done through the use of a magnet, which allows the change of position and/or integration at any time.

Installation:

On ZERO or f_90/140 system.



Dimension:

SPOT LED 70

Ø = 65 mm H = 82/100mm

Finishes:



SPOT LED 70 6W 615lm 102,5lm/W 350mA 3000°K CRI>90
SPOT LED 70 9W 1025lm 114lm/W 500mA 3000°K CRI>90

Available with DALI dimmeration.



Available in 2700°K and 4000°K version.

SPOT LED 70

